



PHGB000013

U.S.A.



INVESTOR IN PEOPLE

**CERTIFIED COPY OF  
PRIORITY DOCUMENT**

The Patent Office  
Concept House  
Cardiff Road  
Newport  
South Wales  
NP10 8QQ




I, the undersigned, being an officer duly authorised in accordance with Section 74(1) and (4) of the Deregulation & Contracting Out Act 1994, to sign and issue certificates on behalf of the Comptroller-General, hereby certify that annexed hereto is a true copy of the documents as originally filed in connection with the patent application identified therein.

In accordance with the Patents (Companies Re-registration) Rules 1982, if a company named in this certificate and any accompanying documents has re-registered under the Companies Act 1980 with the same name as that with which it was registered immediately before re-registration save for the substitution as, or inclusion as, the last part of the name of the words "public limited company" or their equivalents in Welsh, references to the name of the company in this certificate and any accompanying documents shall be treated as references to the name with which it is so re-registered.

In accordance with the rules, the words "public limited company" may be replaced by p.l.c., plc, P.L.C. or PLC.

Re-registration under the Companies Act does not constitute a new legal entity but merely subjects the company to certain additional company law rules.



Signed


*Hevens.*

Dated 20 September 2000

**THIS PAGE BLANK (USPTO)**

**Request for grant of a patent**

*(See notes on the back of this form. You can also get an explanatory leaflet from the Patent Office to help you fill in this form)*



The Patent Office  
Cardiff Road  
Newport  
Gwent NP9 1RH

1. Your reference PHGB 000013

---

2. Patent application number  
*(The Patent Office will fill in this part)* **0003306.8** **15 FEB 2000**

---

3. Full name, address and postcode of the or of each applicant *(underline all surnames)* KONINKLIJKE PHILIPS ELECTRONICS N.V.  
GROENEWOUDSEWEG 1  
5621 BA EINDHOVEN  
THE NETHERLANDS  
  
 Patents ADP Number *(if you know it)* 7419294001  
  
 If the applicant is a corporate body, give the country/state of its incorporation THE NETHERLANDS

---

4. Title of the invention CONTROL OF INTERCONNECTED AUDIO/VIDEO DEVICES

---

5. Name of your agent *(if you have one)* ANDREW GORDON WHITE  
 "Address for service" in the United Kingdom to which all correspondence should be sent *(including the postcode)* Philips Corporate Intellectual Property  
Cross Oak Lane  
Redhill  
Surrey  
RH1 5HA  
  
 Patents ADP number *(if you know it)* 7133473002

---

6. If you are declaring priority from one or more earlier patent applications, give the country and the date of filing of the or of each of these earlier applications and *(if you know it)* the or each application number
 

	Country	Priority Application number <i>(if you know it)</i>	Date of filing <i>(day/month/year)</i>

---

7. If this application is divided or otherwise derived from an earlier UK application, give the number and the filing date of the earlier application
 

	Number of earlier application	Date of filing <i>(day/month/year)</i>

---

8. Is a statement of inventorship and of right to grant of a patent required in support of this request? *(Answer "Yes" if:*

a) any applicant named in part 3 is not an inventor, or

b) there is an inventor who is not named as an applicant, or

c) any named applicant is a corporate body.

See note (d))

YES

9. Enter the number of sheets for any of the following items you are filing with this form.  
Do not count copies of the same document.

Continuation sheets of this form

Description  
Claims(s)  
Abstract  
Drawings

7 (x2)

2 (x2)

1 (x2)

3 (x2) + 3

10. If you are also filing any of the following, state how many against each item:

Priority Documents

Translations of priority documents

Statement of inventorship and right

to grant of a patent (*Patents Form 7/77*)

Request for preliminary examination and

search (*Patents Form 9/77*)

Request for substantive examination

(*Patents Form 10/77*)

Any other documents

(*Please specify*)

11.

I/We request the grant of a patent on the basis of this application.

Signature

Date 14/2/00

12. Name and daytime telephone number of person to contact in the United Kingdom

01293 815299

(A. G. WHITE)

### Warning

After an application for a patent has been filed, the Comptroller of the Patent Office will consider whether publication or communication of the invention should be prohibited or restricted under Section 22 of the Patents Act 1977. You will be informed if it is necessary to prohibit or restrict your invention in this way. Furthermore, if you live in the United Kingdom, Section 23 of the Patents Act 1977 stops you from applying for a patent abroad without first getting written permission from the Patent Office unless an application has been filed at least 6 weeks beforehand in the United Kingdom for a patent for the same invention and either no direction prohibiting publication or communication has been given, or any such direction has been revoked.

### Notes

- If you need help to fill in this form or you have any questions, please contact the Patent Office on 0645 500505.
- Write your answers in capital letters using black ink or you may type them.
- If there is not enough space for all the relevant details on any part of this form, please continue on a separate sheet of paper and write "see continuation sheet" in the relevant part(s). Any continuation sheet should be attached to this form.
- If you have answered "Yes" *Patents Form 7/77* will need to be filed.
- Once you have filled in the form you must remember to sign and date it.
- For details of the fee and ways to pay please contact the Patent Office.

## DESCRIPTION

**CONTROL OF INTERCONNECTED AUDIO/VIDEO DEVICES**

5           The present invention relates to systems composed of a plurality of devices clustered for the exchange of data, preferably audio and/or video data and control messages, via wired or wireless link and, in particular although not essentially, to such systems where it is desired to control different ones of the devices via a wired or wireless remote control device. The invention further  
10 relates to devices for use in such systems.

          Networking or interconnection of devices has long been known and used, starting from basic systems where different system functions have been provided by separate units, for example hi-fi or so-called home cinema  
15 systems. A development has been the so-called home bus systems where a greater variety of products have been linked with a view to providing enhanced overall functionality in for example domestic audio/video apparatus coupled with a home security system and the use of telephone. An example of such a home bus system is the domestic digital bus (D2B), the communications  
20 protocols for which have been issued as standard IEC 1030 by the International Electrotechnical Commission in Geneva, Switzerland. The D2B system provides a single wire control bus to which all devices are interfaced with messages carried between the various devices of the system in a standardised form of data packet.

25           A particular problem that can occur with interconnected systems such as hi-fi and home cinema, particularly when assembled from components of different manufacturers, is the proliferation of remote control devices for controlling the respective connected units. One known way in which this problem has been tackled is by the provision of an "intelligent" remote control  
30 that can be programmed or reconfigured by a user to operate devices other than that for which it was first provided: an example of this is given in United States patent 4,626,848 (Ehlers).

Whilst a remote control that learns is a step forward, it encounters a further problem in terms of the number of control function keys it must carry. In effect, the problem becomes one of how to control a first device using remote control which does not have all the function keys for that device on it. For example, in the case of a digital versatile disc (DVD) player to be controlled using a remote control intended for a digital television (DTV), a DTV remote control is unlikely to have all the necessary DVD keys: while the simple Play, Stop, Fast Forward, Rewind and Record keys may be present, other DVD-specific buttons like Camera Angle will probably not be present.

Where a large number of functions are required to be controlled from a single remote device, one option for keeping the number of physical controls down is to have soft keys onto which are mapped selected ones from a specific set of functions. An example of such a control mechanism is given in United States patent 5,517,257 (Dunn et al) where a four-way selector device on as remote control selectively has groups of four control features assigned to it, with the current assignment at any given time being shown on a television or other display screen forming part of the controlled system. Whilst this arrangement may help to reduce the numbers of control buttons or switches on the remote control, it does require all the mappable functions to be known and pre-stored.

It is accordingly an object of the present invention to provide a networked system of devices including a facility for control of all devices through a single remote control arrangement, which arrangement is capable of ready adaptation to accommodate new devices with additional features.

In accordance with the present invention there is provided a local communication system comprising a plurality of devices interconnected for the communication of data, wherein one of said devices is a display device arranged to display data from one or more other devices of the system, and wherein one of said devices is a remote control device carrying a first group of controls for controlling respective operational functions of a device of the system, the system including:

selector means for identifying a selected device of the system to be controlled by user operation of said remote control device; and

virtual control means to determine which operational functions of said selected device do not have a corresponding control on said remote control device, and generate on said display device a user actuatable simulacrum of a control means for each such operational function.

By generation of the simulacra, which may simply comprise user-selectable graphic icons representing the additional functionality, the capabilities of the remote control are effectively extended through the provision of physical controls for functions it was originally designed to support, and virtual (i.e. on-screen) controls for functions added subsequently.

Generation of the simulacrum or simulacra may be handled by the display device based on data from said selected device, or by reference to stored data, which data is accessed by reference to the device type of the selected type: alternately, it may be generated by said selected device and transmitted as display data to said display device. With this latter arrangement, the display device is not required to either hold or acquire data defining the simulacra and related functionality - it simply needs to support the display of remotely originating icons or simulacra and be configured to indicate to their originating device when they have been selected by a user.

Further features and advantages of the present invention are defined in the attached claims (the disclosure of which is incorporated herein by reference) or will become apparent from reading of the description of preferred embodiments of the invention, given by way of example only and with reference to the accompanying drawings, in which:

Figure 1 represents a digital versatile disc (DVD) player and digital television (DTV) coupled by data link;

Figure 2 schematically represents the provision of virtual controls from a first selected device in an interconnected system; and

Figure 3 shows the change in generated virtual controls when a different device in the arrangement of Figure 2 is selected.

A first arrangement of interconnected devices is shown in Figure 1, with DVD player 10 and DTV 12 being linked via bus 14 supporting communication in accordance with IEEE Standard 1394 connect and communications protocols. In the following example, reference is made to IEEE 1394, and the disclosure of the specification of this protocol is incorporated herein by reference. As will be recognised by the skilled reader, however, conformance with this or any other such protocol is not essential to the operation of the present invention.

The functional features of the DVD 10 include a presentation stage 16 which reads data from disc 18 and passes it via an encoder and decoder stage 20 to output through an interface 22 between the DVD player and the 1394 bus 14. From the bus 14, the interface 22 receives control commands which it passes to a navigation stage 24 (directing the reading of data via presentation stage 16), to a player set-up control 26 and optionally, where provided, to a panel subunit 28. Control and display of control functions for the DVD player is via front panel display processor 30 and remote control device 32, with the display processor 30 being coupled to navigation 24 and set-up 26 stages.

Within DTV 12, video signals from the bus 14 are received by an interface 34 coupled to display screen 36. Also provided is a receiver 38 for signals from a remote control device 40, which receiver is coupled to a command processor 42 which handles not only internal control functions for the DTV 12, but also the generation of control commands to be sent to DVD 10. In dependence on the means selected for generation of virtual keys, a key renderer or panel subunit controller 44 may be provided, as will be described in more detail below. In the latter case, an asynchronous link 46 is provided from the subunit controller to interface 34.

As will now be described with reference to Figures 2 and 3, which schematically represents the DVD 10 and DTV 12 linked via bus 14 of Figure 1, together with a further device 50 such as a satellite receiver, the interconnected devices provide a local communication system, wherein the display device 12 is arranged to display data from the other devices 10, 50 of



the system. The remote control 40 for the DTV 12 carries a first group of controls, as shown by number keys 1..9, 0 together with up/down select keys 52, audio mute button 54 and seven further function keys indicated as A to G, which keys control respective operational functions of DTV 12, such as volume, contrast and so forth. Control logic of the system, suitably but not necessary provided by the DTV command processor 42 (Fig. 1), provides a selector means for identifying a selected device of the system 10, 12, 50 to be controlled by user operation of the remote control 40. In the example of Figure 2, the selected device is the DVD player 10 which has operational functions illustrated as C, D, H, J, K, and L. The functions C and D are common to those supported by the DTV 12 (for example contrast and volume) and no additional controls are required on remote control 40 to operate these functions of the DVD 10 via the bus 14.

For the remaining control functions H, J, K, and L of DVD 10, the remote control 40 does not have a suitable control. Instead, control logic of the system (again optionally involving command processor 42, together with key renderer or panel subunit controller 44), provides a virtual control means to determine which operational functions of the user-selected device (DVD 10) do not have a corresponding control on the remote control 40. For these functions H, J, K, L, the control logic generates on the display 36 a user actuatable simulacrum - indicated generally at 56 - of a control means for each such operational function. These simulacra 56 may be icons displayed on screen, optionally overlaying anything currently shown, and may be selected by means of the remote control 40, optionally being highlighted (as for J) as the user operates up/down keys 52 to step through the icons.

Figure 3 illustrates the case where the selected device is satellite receiver 50. Here, device functions D, E, and F are shared with the DTV 12, and so only "new" functions L, M and N have simulacra generated on screen 36, as indicated at 58. As may be seen, function L is common to both DVD 10 and satellite receiver 50: whether any savings may be made in view of this will depend on how the simulacra are generated, as will be described below.

In order to generate the simulacra, there are three options, as follows:

1. Local DVD Key renderer in the DTV
2. Panel Subunit
3. DVD Player generates OSD for DVD-specific keys

5       Option 1 – Virtual DVD Keys generated locally in the DTV 12. These virtual extra keys are drawn by the DTV on the DTV screen 36 as shown at 56 in Figure 2, with the user navigating with the DTV navigation keys 52. The benefits of this option are that the DTV knows which keys are on its Remote Control and therefore knows which virtual keys need to be provided on the  
10 screen. This allows a DTV manufacturer to put more DVD controls on a DTV RC if needed, but does not rely on the standardisation of a known set of DVD keys on the DTV Remote Control. Also, the virtual key display 56 can be moved around on the DTV screen 36 to suit the video content (like the “PIP Position” key).

15       Against these benefits is the requirement for implementation of a drawing engine for the DVD display and relatively tight restrictions on assigning meanings to different keystrokes and combinations of strokes.

      Option 2 – Panel Subunit. In this option, the look and layout for the extra keys (i.e. those DVD keys not present on the DTV RC) are described to  
20 the DTV by the Panel Subunit 28 in the DVD 10. The DTV draws the user interface on the screen (using the DTV’s Panel Subunit Controller 44) and the user has to navigate using the DTV navigation keys.

      This option has benefits in terms of better control over the look and layout of the display than option 1, together with support for manufacturer-  
25 specific keys and multi-function key combinations. As before, the virtual key display can be moved around on the DTV screen to suit the video content. Against this must be weighed the need for (and cost of) a panel subunit in the DVD Player and a panel subunit controller in the DTV.

      Option 3 – DVD Player generates OSD for DVD-specific keys. This  
30 uses the existing on-screen display (OSD) generator in the DVD player, the DVD generates its own menu or OSD which is rendered in the DVD memory

and transferred as a bitmap to the DTV using the 1394 Asynchronous service. The user has to navigate with the DTV navigation keys.

The advantages of this arrangement are minimal impact on the DTV, no need for panel subunit, local key renderer, etc. Also, the DVD Player has  
5 complete control over display and uses the existing OSD generator in the DVD player. Multi-function key combinations (e.g. right arrow is also Fast Forward) may be defined by the DVD manufacturer.

Against this is the need for extra software in DVD Player, and the need for a  
10 bitmap to be generated in the DVD player's memory and transferred as a bitmap. Also, the virtual display is potentially much larger than the simple icon display, and it may not be possible for virtual key display to be moved around on the DTV screen to suit the video content.

From reading the present disclosure, other modifications and variations  
15 will be apparent to persons skilled in the art, including equivalents and features which are already known in the field of bus-connected and cordless communication systems and components and which may be used instead of or in addition to features already disclosed herein.

In the foregoing we have described a local communication system which comprises a plurality of devices interconnected for the communication  
20 of data. One of the devices is a display device arranged to display data from one or more other devices of the system, and one of said devices is a remote control carrying a first group of controls for controlling respective operational functions of a device of the system. The system is configured to identify a  
25 selected device of the system to be controlled by user operation of said remote control device, and to determine which operational functions of that selected device do not have a corresponding control on the remote control. For such functions, the system generates on the display device a user actuable simulacrum of a control for that function.

## CLAIMS

1. A local communication system comprising a plurality of devices  
5 interconnected for the communication of data, wherein one of said devices is a display device arranged to display data from one or more other devices of the system, and wherein one of said devices is a remote control device carrying a first group of controls for controlling respective operational functions of a device of the system, the system including:  
10 selector means for identifying a selected device of the system to be controlled by user operation of said remote control device; and  
virtual control means to determine which operational functions of said selected device do not have a corresponding control on said remote control device, and generate on said display device a user actuable simulacrum of a  
15 control means for each such operational function.
2. A system as claimed in Claim 1, wherein said simulacrum is generated by said display device based on data from said selected device.
- 20 3. A system as claimed in Claim 1, wherein said simulacrum is generated by said display device by reference to stored data, which data is accessed by reference to the device type of the selected type.
4. A system as claimed in Claim 1, wherein said simulacrum is  
25 generated by said selected device and transmitted as display data to said display device.
5. A system as claimed in any of Claims 1 to 4, wherein said remote control device has a corresponding control for all functions of said  
30 display device.

6. A system as claimed in Claim 5, wherein said remote control device includes a control for selectively actuating a displayed simulacrum.

7. A system as claimed in Claim 6, wherein said display device is  
5 arranged to display a plurality of simulacra and the remote control device comprises means for stepping through said simulacra and selecting one or more thereof.

8. A system as claimed in any of Claims 1 to 7, wherein  
10 interconnection between two or more of the devices is provided by a wireless link.

9. A system as claimed in any of Claims 1 to 7, wherein  
interconnection between two or more of said devices is via a digital data  
15 communication bus to which the devices are respectively interfaced, with said data being carried thereupon as discrete data packets.

10. Data processing apparatus comprising the technical features of  
said virtual control means in a system as claimed in any of Claims 1 to 9.  
20

11. A local communications system comprising a plurality of devices  
interconnected for the communication of data substantially as hereinbefore  
described with reference to the accompanying drawings.

25 12. A data processing apparatus comprising a virtual control means  
and for use as a device in a system comprising a plurality of devices  
interconnected for the communication of data substantially as hereinbefore  
described with reference to the accompanying drawings.

## ABSTRACT

**CONTROL OF INTERCONNECTED AUDIO/VIDEO DEVICES**

5

A local communication system comprises a plurality of devices (10, 12, 50) interconnected (14) for the communication of data. One of the devices (12) is a display device arranged to display data from one or more other devices of the system, and one of said devices (40) is a remote control carrying a first  
10 group of controls (A..G) for controlling respective operational functions of a device (10) of the system. The system is configured to identify a selected device (10) of the system to be controlled by user operation of said remote control device (40), and to determine which operational functions of that selected device do not have a corresponding control (C, D) on the remote  
15 control. For such functions, the system generates on the display device a user actuatable simulacrum 56 of a control for that function (H, J, K, L).

(Figure 2)

20




FIG. 1

**THIS PAGE BLANK (USPTO)**






FIG. 2

**THIS PAGE BLANK (USPTO)**




FIG. 3

**THIS PAGE BLANK (USPTO)**